


BUS Cables

E-BUS / KNX fixed installed



PVC + FRNC



Type Cable structure

Inner conductor:
Core insulation:
Core colours:
Stranding element:
Separator:
Shielding 1:
Total shielding:
Drain wire:
Outer sheath material:
Cable external diameter:
Outer sheath colour:

2-pairs 2x2x0.8 mm

Copper, bare
PVC
wh, ye, rd, bk
Star quad
Polyester foil over stranded bundle
-
Al-Foil
yes
PVC
app. 6,2 mm \pm 0,3 mm
Blue Lilac similar to RAL 4005

2-pairs 2x2x0.8 mm

Copper, bare
PE
wh, ye, rd, bk
Star quad
Polyester foil over stranded bundle
-
Al-Foil
yes
FRNC
app. 6,2 mm \pm 0,3 mm
Blue Lilac similar to RAL 4005

Electrical data

Characteristic impedance:
Conductor resistance, max.:
Insulation resistance, min.:
Loop resistance:
Mutual capacitance:
Test voltage:

100 Ohm
36,6 Ohm/km
0,1 GOhm x km
73,2 Ohm/km max.
120 nF/km nom.
4 kV

100 Ohm
36,6 Ohm/km
0,1 GOhm x km
73,2 Ohm/km max.
120 nF/km nom.
4 kV

Technical data

Weight:
bending radius, repeated:
Operating temperature range min.:
Operating temperature range max.:
Caloric load, approx. value:
Copper weight:

app. 64 kg/km
95 mm
-30°C
+70°C
0,90 MJ/m
25,00 kg/km

app. 54 kg/km
95 mm
-30°C
+70°C
0,58 MJ/m
25,00 kg/km

Norms

Applicable standards:

EIB/KNX standard
Flame-retardant acc. IEC 60332-2-1

EIB/KNX standard
Halogen-free acc. to 60754-1
Flame-retardant acc. IEC 60332-2-1

Application

HELUKABEL® E-BUS EIB/KNX PVC for fixed installation. The E-Bus cable is intended for transmission of bus signals in intelligent building systems. The cables ensure perfect communication in compliance with EIB regulations. They can be installed over, in and under plaster, in conduits and cable channels, in dry, damp and wet rooms as well as outdoors - if protected from direct sunlight. Wiring together with high-power cables is possible without limitation. The EIB/KNX bus can be used to control lighting, blinds, heating, ventilation, indicator boards etc.

Part no.

81081, E-BUS / KNX

80826, E-BUS / KNX

Dimensions and specifications may be changed without prior notice.